

# DUCHESNE COUNTY MONUMENT SURVEY RECORD

LINE	BEARING	DISTANCE
L1	N 01°34'48" W	32.82'
L2	N 05°18'35" E	31.05'
L3	N 09°15'50" E	33.37'
L4	S 76°58'53" E	43.97'
L5	S 08°48'25" E	17.16'

NAIL & WASHER  
IN POWER POLE

PIPE BRACE CORNER

PIPE BRACE CORNER

SECTION  
CORNER

N 90°00'00" W  
2645.70'

PIPE FENCE CORNER

NAIL & WASHER  
IN POWER POLE

T1S R5W

SEC 24

1/4

SEC 25

U.S.B.&M.

J-23



NORTH

SCALE: 1"=30'

## DESCRIPTION OF CORNER EVIDENCE FOUND

FOUND 1/4" REBAR UNDER THE ROAD SURFACE AS PER PREVIOUS COUNTY TIE SHEET.

## DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THE CORNER

SET 2 1/2" ALUMINUM COUNTY MONUMENT AT CORNER LOCATION, STAMPED;



## STATE PLANE COORDINATE DATA

## CERTIFICATION

I Jerry D. Allred, Professional Land Surveyor, State of Utah, do hereby certify that I have performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve same

Date 17 DEC '03

Jerry D. Allred, Professional Land Surveyor  
Certificate No. 148951  
Duchesne County Surveyor



SEND 18 DEC 03